


ZIP MACHINE . NOSO MX 264Z



Machine to tape and cut decorative or waterproofing tapes over zippers up to 40 mm width (maximum tape width 35 mm).

The machine is equipped with a lower guide support for continuous taping, and a tape tensioner to simplify the taping process. The longitudinal cut is obtained by using the cutting device supplied with the machine.




HEAT HAS NEVER BEEN SO GREEN
less consumption, better efficiency



MACHINE KEY FEATURES



- Pressure up to 35 kg. with top adhesion and waterproofing performance
- 40 mm nozzle
- 40 mm roller
- Motorized top roller for overlapping seams or thick fabrics
- Garments can be taped both open and closed
- It can deal also with curves
- High speed
- Even heat distribution
- No scorched fabrics
- Top quality components
- Low and easy maintenance
- Tapes of different quality can be used, maximum width 35 mm

PARTS OF EQUIPMENT



KIT lower guide support for vertical arm continuous taping/zipper set up

The kit allows a continuous taping processing. The customized guide will be provided separately, depending on zipper size/width.



KIT Longitudinal zipper cutter - continuous cut for taped zipper

The kit applied to the vertical arm allows a continuous longitudinal cut of the applied tape. The correct position of the blade is adjustable and the zipper tension is guaranteed by a manual tensioner.

FRAMISITALIA



BONDING TECHNOLOGY

ZIP MACHINE . NOSO MX 264Z

TECHNICAL IMPROVEMENT

- .increase adhesion
- .increase speed
- .increase production
- .reduce thermal stress of the machine
- .reduce thermal stress on the fabric
- .minimize electricity consumption
- .greater performance with less quantity of air improving also the comfort for the operator
- .standby mode



HEAT HAS NEVER BEEN SO GREEN
less consumption, better efficiency



BASE MACHINE DESCRIPTION

- .base machine with 1 heater
- .spot lamp
- .drawer
- .vertical roll support
- .tensioner metering device
- .teflon down wheel 40 mm, grooved depending on customer's need
- .silicone-rubber wheel group 40 mm-70SH (soft)
- .nozzle 40 mm (tape max width 35 mm)
- .vertical Arm Neutral gear
- .protection screen
- .white table with beech borders 120x60x4
- .table support structure
- .pedals
- .16A 3 poles socket
- .tape guide 20x1 mm
- .screwdriver 2,5
- . Manual

TECHNICAL INFO FOR INSTALLATION

Dimension and weight

h. 1100 x 550 x H.1550 mm - 80 Kg

Pneumatic connection - all connections on the left side

Fast junction diam 8 mm

Maximum air flow: 80 l/min - average consumption: 45 to 55 l/min

Input air pressure: 5.5 bar (0.55 MPa)

Air quality: dry air in accordance to DIN 8573-1 with dew point + 3° C not lubricated

Electric connection

Nominal voltage: 230 Vac

Nominal frequency: 50 Hz / 60 Hz

Nominal power requirements: 1400 W

THE LOWEST CONSUMPTION IN THE WORLD OF BONDING

Average consumption for standard applications

Electricity consumption: 0.45 kw/h - CO₂ emission: 129 gr/h - Compressed air consumption: 45 to 55 l/min

The machines complies to technical rulings: Machinery Directive 2006/42/CE, Electromagnetic Compatibility CEE 2004/108/CE and CEI EN 60204-1:2006, Low Tension Directive 2006/95/CE, UNI EN 414:2002, UNI EN ISO 12100:2010, UNI EN ISO 13857:2008, UNI EN ISO 13850:2007, UNI EN ISO 11202:2007

FRAMISITALIA
ITALY • HONG KONG • USA

FRAMIS ITALIA SpA . Via dell'Agricoltura 9/15 - 20083 Vigano di Gaggiano - Milan - Italy - www.framis.it

FRAMIS ITALIA HK . Ltd Unit G on 7/f - Kwai Shun Industrial Centre - No. 51-63 Container Port Road - Kwai Chung - New Territories - Hong Kong