

# WELD&FOLD - TAPING MACHINE . NOSO MX 210

Machine for making folded edges in a single operation, ideal for well finished edges, especially on fabrics that fray easily. The machine is equipped with an electronic tape tensioner, to handle gathering.

By taking the folding guide off, the machine becomes a taping machine, for decorative or reinforcement tapings on open or closed fabrics.



**HEAT HAS NEVER BEEN SO GREEN**  
less consumption, better efficiency



## MACHINE KEY FEATURES

- Ideal for fabrics that fray easily and with slight curling
- Electronic tape tension regulation
- Can handle gathering
- It can deal also with curves
- Rubber conveyor belt
- High speed
- Both open and closed garments
- Even heat distribution
- No scorched fabrics
- Top quality components
- Low and easy maintenance
- Tapes of different quality and widths
- Recommendable tape width: from 8 to 25 mm
- Maximum load: 11 kg

## TECHNOLOGY



LW 004 . REDUCED FOLDED EDGE



LW 301 . DECORATIVE TAPING



LW 303 . REINFORCEMENT TAPING

## APPLICATIONS



FRAMISITALIA

 BONDING TECHNOLOGY

# WELD&FOLD - TAPING MACHINE . NOSO MX 210

## TECHNICAL IMPROVEMENT

- .increase adhesion
- .increase speed
- .increase production
- .reduce thermal stress of the machine
- .reduce thermal stress on the fabric
- .minimize electricity consumption
- .greater performance with less quantity of air improving also the comfort for the operator
- .standby mode



**HEAT HAS NEVER BEEN SO GREEN**  
less consumption, better efficiency



## BASE MACHINE DESCRIPTION

- .base machine with 1 heater
- .spot lamp
- .drawer
- .vertical roll support
- .tensioner metering device
- .silicone rubber wheel group 17 mm - 35SH (soft)
- .30 mm nozzle
- .horizontal arm
- .protection screen
- .white table with beech borders 120x60x4
- .table support structure
- .pedals
- .16A 3 poles socket
- .folding guide 5 mm
- .tape guide 10x1 mm
- .screwdriver 2,5 mm
- .Manual

## TECHNICAL INFO FOR INSTALLATION

### Dimension and weight

h. 1100 x 550 x H.1550 mm - 80 Kg

### Pneumatic connection - all connections on the left side

Fast junction diam 8 mm

Maximum air flow: 80 l/min - average consumption: 45 to 55 l/min

Input air pressure: 5.5 bar (0.55 MPa)

Air quality: dry air in accordance to DIN 8573-1 with dew point + 3° C not lubricated

### Electric connection

Nominal voltage: 230 Vac

Nominal frequency: 50 Hz / 60 Hz

Nominal power requirements: 1400 W

## THE LOWEST CONSUMPTION IN THE WORLD OF BONDING

Average consumption for standard applications:

Electricity consumption: 0.45 kw/h - CO<sub>2</sub> emission: 129 gr/h - Compressed air consumption: 45 to 55 l/min

The machines complies to technical rulings: Machinery Directive 2006/42/CE, Electromagnetic Compatibility CEE 2004/108/CE and CEI EN 60204-1:2006, Low Tension Directive 2006/95/CE, UNI EN 414:2002, UNI EN ISO 12100:2010, UNI EN ISO 13857:2008, UNI EN ISO 13850:2007, UNI EN ISO 11202:2007

**FRAMISITALIA**  
ITALY · HONG KONG · USA

FRAMIS ITALIA SpA . Via dell'Agricoltura 9/15 - 20083 Vigano di Gaggiano - Milan - Italy - [www.framis.it](http://www.framis.it)

FRAMIS ITALIA HK . Ltd Unit G on 7/f - Kwai Shun Industrial Centre - No. 51-63 Container Port Road - Kwai Chung - New Territories - Hong Kong