



EDGE BINDING MACHINE - DOUBLE TECHNOLOGY MX 208 D


The only edge binding machine on the market that allows the PERMANENT BONDING: you don't need to pass through the heat press to finish the application! It means more productivity, less waste of time, less equipment in your factory*. Such performance can be achieved combining two technologies, tape tension and differential speed, that are settable to work separately or simultaneously. Taking advantage of these technologies, the machine offers new and improved results, such as better handling of wide range of fabrics and tapes and great managing of both flat and gathering applications, on light and thick fabrics.

HIGHLIGHTS


- Permanent bonding*
- Increasing of productivity (heat press step is not needed*)
- Best performance on stretch fabrics
- Motor driven wheels with differential speed capability
- Tape tension regulation
- Great results on both flat and gathered applications
- Possibility to operate on open and closed garments
- Good for stretch and firm fabrics
- It can deal also with curves
- Edging of both thick and light fabrics



APPLICATIONS






EDGE BINDING



DOUBLE FABRIC EDGE BINDING
First step required: MU 280

TECHNOLOGY





EDGE BINDING MACHINE - DOUBLE TECHNOLOGY MX 208 D

FEATURES

- Small wheels to simplify handling
- High speed
- No scorched fabrics
- Low and easy maintenance
- Recommendable tapes width: 16 mm
- Minimize electricity consumption
- Greater performance with less quantity of air
- Standby mode



HEAT HAS NEVER BEEN SO GREEN
less consumption, better efficiency

Average consumption for standard applications

Electricity consumption: 0.45 kw/h

CO₂ emission: 129 gr/h

Compressed air consumption: 45 to 55 l/min

TECHNICAL INFO FOR INSTALLATION

Dimension and weight

h. 1100 x 550 x H.1550 mm - 80 Kg

Pneumatic connection - all connections on the left side

Fast junction diam 8 mm

Maximum air flow: 80 l/min - average

consumption: 45 to 55 l/min

Input air pressure: 5.5 bar (0.55 MPa)

Air quality: **dry air** in accordance to DIN 8573-1 with dew point + 3° C not lubricated

Electric connection

Nominal voltage: 230 Vac

Nominal frequency: 50 Hz / 60 Hz

Nominal power requirements: 1400 W

BASE MACHINE DESCRIPTION

Wheel speed with differential

Base machine with 1 heater

Spot lamp

Drawer

Vertical roll support

Tensioner metering device

Side arm

Upper silicone rubber wheel group 12 mm - 70SH (hard)

Lower silicone rubber wheel 14 mm - 70SH (hard)

Nozzle c-binding

Protection screen

White table with beech borders 120x60x4

Table support structure

Pedals

16A 3 poles socket

Edge binding guide 16mm

Specifications and appearance are subject to change without prior notice for improvement

The machines complies to technical rulings: Machinery Directive 2006/42/CE, Electromagnetic Compatibility CEE 2004/108/CE and CEI EN 60204-1:2006, Low Tension Directive 2006/95/CE, UNI EN 414:2002, UNI EN ISO 12100:2010, UNI EN ISO 13857:2008, UNI EN ISO 13850:2007, UNI EN ISO 11202:2007

* The permanent bonding performance can vary depending on the fabrics used, and/or the application wanted.